

# **ALL IN ONE. TIMES TWO.**

VeriFone's VX 820 DUET is the perfect combination – a stylish PIN pad along with a functional base to create a feature-rich countertop device. Together, merchants and consumers get everything they need in one device. All on the proven VX platform.



#### Processor

400 MHz ARM11 32-bit RISC processor

#### Memory

160 MB (128 MB of Flash, 32 MB of SDRAM) standard, designed to support up to 500 MB Optional micro SD Flash memory card

#### Display

240x320 pixel color TFT (QVGA) supports up to 26 lines x 26 characters

## **PCI SECURITY**







## **DUAL DESIGN, DOUBLE THE EASE OF USE**

- Dual-purpose design combines a countertop payment device with an ergonomic, programmable PIN pad
- Large, bright, blue backlit keypad is exceptionally user-friendly for both merchants and consumers
- Fits a large, crystal-clear, 3.5", color, touch display and intuitive card handling capabilities into a sleek device
- Base has compact footprint that securely cradles the PIN pad
- Includes a built-in, thermal printer conveniently tucked away plus USB or serial to simplify peripheral support and dial or Ethernet for connection needs

## **EXPANDED CAPABILITIES WITHIN EASY REACH**

- Available with VeriFone's NFC software technology enabling full flexibility to manage multiple NFC mobile wallets, apps and programs.
- 400 MHz ARM 11 processor combined with 160 MB of memory provides increased processing speeds and ability to run an unbeatable range of applications
- Designed to support up to 500 MB of memory, offering almost limitless capacity for loyalty-building and value-added applications
- Accepts all forms of payment from credit and PIN-based debit to EMV smart card transactions

### RAISING THE BAR ON SECURITY AND RELIABILITY

- Built with durable components such as a smart card reader that takes 500,000 insertions and a keypad that withstands more than one million key presses
- Provides end-to-end encryption with VeriShield Total Protect, secured by RSA, to maximize protection against fraud and misuse

#### Magnetic Card Reader

Triple track (tracks 1, 2, 3), high coercivity, bi-directional

### **Primary Smart Card**

ISO 7816, 1.8V, 3V, 5V; synchronous and asynchronous cards; EMV Level 1 and 2 Type approved

### SAM Card Reader

3 Security Access Modules (SAMs)

### Peripheral Ports

USB host and RS-232 to support peripheral devices Telco and Ethernet ports to support communications

#### Printer

Integrated thermal printer with graphics capabilities, 18 lines per second, 24 or 32 columns, standard paper roll 58 mm (2.25 in.) x 25M, single ply

#### Moden

Standard 56 kbps modem Bell 103/212a, CCITT V.21/V.22/V.22bis/V.32/V.32bis (300/1200/2400/9600/14400/33.6/56 and HC FastConnect for 1200bps)

#### Protocols

Application selects between asynchronous protocols (Visa 1, Visa 2 and others) and synchronous protocols (including ISO 8583/SDLC)

#### Security

SSL v3.0, 3DES encryption, Master/Session and DUKPT key management; VeriShield file authentication; PCI PTS 3.X approved

### Physical

Length: 178mm (7.01in.); Width: 98mm (3.86in.); Height: 109mm (4.3in.); Weight: terminal, 735g (1.62lbs.) Full shipping, 1800g (3.96lbs.)

#### Environmental

0° to 50° C (32° to 122° F) operating temperature; 5% to 90% relative humidity, non-condensing

#### Voltage

AC input 100 – 240 VAC, 50/60 Hz; DC output 8.6 – 9.4 VDC, 4.0 Amp

## Contactless Applications

MasterCard PayPass M/Chip | MasterCard PayPass MagStripe | Visa payWave MSD | Visa payWave qVSDC | Discover Zip | American Express ExpressPay | Pass-through access to ISO 14443-4 and MiFare card, for direct host terminal based application access | Secure SoftSAM | Hardware SAM optional

#### **NFC Applications**

Support for ISO 18092

